



WaterMark Level 1

Certificate of Conformity

Australian Certification Services Pty Ltd grants to the WaterMark User:

Natural Action Technologies Inc AHA Structured Water

Trading as AHA Structured Water

the right to use the WaterMark as shown above in conjunction with the Certificate No. on product/s as identified in the WaterMark Schedule and as listed on the WaterMark database www.abcb.gov.au/Product-Certification/WaterMark-Certification-Scheme which have been shown to comply with the relevant Standard/s and level of certification referred to below. The WaterMark User is granted a licence to use the WaterMark subject to the rules governing the use of the WaterMark.

Product Type: Structured Water Unit
Brand: AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES
Evaluated to: WMTS 103:2016 Water treatment systems (other than those specified in AS/NZS 3497)

Paul Greig
General Manager

Issue Date: 9th June 2017
Initial Issue Date: 9th June 2017
Expiry Date: 8th June 2022

Certificate No.: 23296

This certificate remains the property of Australian Certification Services Pty Ltd

WaterMark Level 1 certification is a conformity assessment scheme based on ISO Guide 67 (system 5)





WaterMark Certification Schedule

The WaterMark User	Natural Action Technologies Inc 1510 S. Koch Ranch Road PB 1449 Cornville Arizona 86325-1449 USA AHA Structured Water ABN: 45 192 440 600 Suite 7/283 Glen Huntly Rd Elsternwick Victoria 3185 AUSTRALIA Website: www.ahastructuredwater.com.au
Certificate Number	23296
Level of Certification	WaterMark Level 1
Certification Standards:	WMTS 103:2016 Water treatment systems (other than those specified in AS/NZS 3497)

Product Listing

Model Identification	Model Name	Brand Name	Product Description
MIE	MINI SHOWER	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Dynamically Enhanced Max. Operating Pressure 1000kPa Max. Operating Temperature 50°C Male/Female Threaded Connection Ends
MIEB	MINI SHOWER	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Dynamically Enhanced Max. Operating Pressure 1000kPa Max. Operating Temperature 50°C Male/Female Threaded Connection Ends
MIO	MINI SHOWER	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Dynamically Enhanced Max. Operating Pressure 1000kPa Max. Operating Temperature 50°C Male/Female Threaded Connection Ends
MIOB	MINI SHOWER	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Dynamically Enhanced Max. Operating Pressure 1000kPa Max. Operating Temperature 50°C Male/Female Threaded Connection Ends



Model Identification	Model Name	Brand Name	Product Description
SSE	SUPER SHOWER	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Dynamically Enhanced Max. Operating Pressure 1000kPa Max. Operating Temperature 50°C Male/Female Threaded Connection Ends
SSO	SUPER SHOWER	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Dynamically Enhanced Max. Operating Pressure 1000kPa Max. Operating Temperature 50°C Male/Female Threaded Connection Ends
LGAO	LARGE GARDEN	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Original Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Male/Female Threaded Connection Ends
LGAE	LARGE GARDEN	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Original Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Male/Female Threaded Connection Ends
MGO	MINI GARDEN	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Original Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Male/Female Threaded Connection Ends
MGOB	MINI GARDEN	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Original Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Male/Female Threaded Connection Ends
MGE	MINI GARDEN	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Original Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Male/Female Threaded Connection Ends
MGEB	MINI GARDEN	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Original Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Male/Female Threaded Connection Ends



Model Identification	Model Name	Brand Name	Product Description
GAE	SMALL GARDEN	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Original Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Male/Female Threaded Connection Ends
GAO	SMALL GARDEN	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Original Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Male/Female Threaded Connection Ends
USE	UNDER THE SINK	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Dynamically Enhanced Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Male Threaded Connection Ends
USO	UNDER THE SINK UNIT	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN15 Plastic Bodied Structured Water Unit Original Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Male Threaded Connection Ends
HOUSE E	WHOLE HOUSE	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN20 Plastic Bodied Structured Water Unit Dynamically Enhanced Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Female Threaded Connection Ends
HOUSE O	WHOLE HOUSE	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN20 Plastic Bodied Structured Water Unit Original Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Female Threaded Connection Ends
COE	COMMERCIAL	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN32/40/50 Plastic Bodied Structured Water Unit Dynamically Enhanced Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Female Threaded Connection Ends



Model Identification	Model Name	Brand Name	Product Description
COO	COMMERCIAL	AHA STRUCTURED WATER/NATURAL ACTION TECHNOLOGIES	DN32/40/50 Plastic Bodied Structured Water Unit Original Max. Operating Pressure 1000kPa Max. Operating Temperature 40°C Female Threaded Connection Ends

AUSTRALIAN CERTIFICATION SERVICES

